

# AG SPRAY & FERTILIZER EQUIPMENT 2017 Equipment Catalog









# "Service is Our Specialty"

Caldwell, Idaho

(208) 454-2288

(800) 443-0809

Pasco, Washington

(509) 545-5855

(800) 788-4453

To Order Call Toll Free: Caldwell, ID 800-443-0809 • Pasco, WA 800-788-4453



# Call G&R for Price & Availability! LESS WEIGHT = LESS COMPACTION

- Weighs 3,000-14,000 lbs less than competing sprayers
- Decreases soil compaction to increase yield potential
  - Lowers operating costs Increases fuel economy





### POWER WHERE AND WHEN YOU NEED IT MOST

Strength, simplicity and savings. The Apache has all three, thanks to its patented POWER-TO-THE-GROUND™ technology.





### **AS 730**

Tank Capacity: 750 Gallons Transmission:

JCB Power Shift 4- speed **Engine**:

Cummins Tier 4F 173 hp

Weight:

19,700 lbs. (approx. dry weight)

Axle Width:

120" Fixed or 120" - 160" Adjustable



### **AS 1030**

Tank Capacity: 1000 Gallons

**Transmission:** 

ZF Power Shift 6 - speed with lock up torque converter

Engine:

Cummins Tier 4F 225 hp

Weight:

20,000 lbs. (approx. dry weight)

**Axle Width:** 

120" Fixed or 120" - 160" Adjustable



### **AS 1230**

Tank Capacity:

1200 Gallons

**Transmission:** 

ZF Power Shift 6 - speed with lock up torque converter

**Engine:** 

Cummins Tier 4F 260 hp

Weight:

21,000 lbs. (approx. dry weight)

AS 1230 XP -- 300 HP

Caldwell, ID 800-443-0809 • Pasco, WA 800-788-4453



# Fiberworks Boom EXCLUSIVE COMPOSITE MATERIAL.

FiberWorks Booms are constructed of exclusive composite material that features superior strength and flexibility to traditional steel tubing. FiberWorks is a lightweight, high impact material that has been field proven over millions of acres. Simply put... FiberWorks is far superior to any boom system on the market today







### BESTWAY V-RIDE™ MAKES THE DIFFERENCE!

V-RIDE™ effectively isolates trailer movement from the boom, resulting in significant performance enhancements which include; increased field speeds of 2-5 mph resulting in up to 25% increased productivity, reduced fuel costs and improved spray pattern control for optimized application accuracy.

The V-RIDE™ system is especially accomplished simply by turning a knob on the suspension control valve located on the sprayer, to "DIAL IN" the preferred boom ride

**Chemical Inductor System** 



AutoGlideXR<sup>TM</sup>
The Affordable Auto Boom
Height Control System



### **Best Way Field-Pro 1850**

1850 gallon - 90' or 100' Fiberworks Booms Adjustable Axles: 88" - 132" or 100" - 144"

100 Gallon Rinse System \* Hypro Clean Load Chemical Inductor

### **Best Way Field-Pro 1600**

1600 gallon - 90' or 100' Fiberworks Booms Adjustable Axles: 88" - 132" or 100" - 144"

100 Gallon Rinse System \* Hypro Clean Load Chemical Inductor

### **Best Way Field-Pro 1200**

1200 gallon - 90' or 100' Fiberworks Booms Adjustable Axles: 80" - 120" or 112" - 152"

100 Gallon Rinse System \* Hypro Clean Load Chemical Inductor
Best Way Field-Pro 1200/80

1200 gallon - 80' Fiberworks Booms

Adjustable Axles: 80" - 120" or 112" - 152"

50 Gallon Rinse System \* Hypro Clean Load Chemical Inductor

### **Best Way Field-Pro 1000**

1000 gallon - 60' or 80' Fiberworks Booms Adjustable Axles: 80" - 120" or 112" - 152"

50 Gallon Rinse System \* Hypro Clean Load Chemical Inductor



The NTX Series will be built in conjunction with the proven Field-PRO IV Series sprayers

and share the same FiberWorks Boom System and patented V-Ride Variable Ride Boom Suspension. The new NTX Series feature a new frame and axle design that allows 60" - 120" wheel spacing in certain models.

Tanks sizes are 1000, 1250 and 1500 gallon with boom sizes of 60', 80', 90' and 100'

A rear mounted 100 gallon rinse system and Hypro CleanLoad Inductor System are standard on all NTX Series Sprayers.

### PRO-MOUNT SPRAYERS

PRO - MOUNT 360

300 Gallon 60' Booms



PRO - MOUNT 460

400 Gallon 60' Booms

### **Product Overview**

Transport width: 12' 9" Length added: 6'2" Hitch type: III 3-point

Weight, empty with rinse system: 2340 lbs (Pro-Mount 360); 2490 lbs (Pro-Mount 460)

### **Features**

Hydraulic Front folding 60' Pro-Flex™ FiberWorks™ Live Hydraulic boom controls

Accumulator boom suspension for smooth, stable boom ride 42" vertical height range of center mast for spraying taller crops 300 gallon polyethylene product tank (Pro-Mount 360) 400 gallon polyethylene product tank (Pro-Mount 460)

Chemical inductor

20" nozzle spacing with single nozzle bodies

(3) TeeJet 450 Boom Section Control Valves Integrated parking stands (4)

2 ½ gallon personal safety water tank

# **MOVE IT. LOAD IT. SPREAD IT.**

**REAR DISCHARGE TENDERS** 

# PROFESSIONAL MATERIAL HANDLING



**MODEL 1600 TENDERS** 

Willmar Truck Mounted 1600 rear discharge tenders are ideal for Commercial fertilizer dealers, Custom applicators and large farming operations. With two large-capacity hoppers that feed into one auger, these tenders can carry nearly any single, drymaterial product and load any applicator or planter at up to two tons per minute. Finish it off with an SRT-2 Roll Tarp Cover.



**16-AND 24-TON SIDESHOOTERS** 

Willmar 16-Ton and
24-Ton side- shooting
Tenders can either be
truck or trailer mounted
and can move up to two
tons of material a minute.
Four or Six compartment
Hoppers that can carry a
variety of materials;
Steep 40-degree sloped
sides for quick
dispensing; largediameter, 10-inch augers
and big hydraulic capacity.

Contact your G & R Sales Representative Today for Pricing and Options

To Order Call Toll Free: Caldwell, ID 800-443-0809 • Pasco, WA 800-788-4453

# Willmar Pull Spreaders



### S - 800

40' or 50' Dual Spinner
7" SS Chain 1"x 1" Mesh
77" Track Width
12 Gauge 409 SS Hopper
Tandem Axle Mounted
To Frame with Leaf
Springs and Hangers



### S - 500 / S - 600

40' or 50' Dual Spinner
7" SS Chain 1"x 1" Mesh
540 rpm Weasler PTO
12 Gauge 409 SS Hopper
Tandem Axle Mounted
To Frame with Leaf
Springs and Hangers

S - 150

25' Dual Spinners
7" SS Chain 1"x 1" Mesh
540 rpm Weasler PTO
12 Gauge 409 SS Hopper
Single Axle
Mounted to Frame













Salford BBI designs and manufactures Fertilizer Spreaders, Lime Spreaders, Litter Spreaders, Compost Spreaders, Rock Spreaders, Aggregate Spreaders, Sand Spreaders, Fertilizer/Lime Spreaders, and Litter, Lime and Shavings Spreaders.





### **Endurance Pull Type Hydraulic Spreader**

The BBI Pull Type Hydraulic Litter Spreaders, Shavings Spreaders, Compost Spreaders, Organics Spreader and Lime Spreaders are available in different hopper styles from 10 to 28 ft long. With the BBI Walking Beam Suspension, your Endurance spreader can handle just about any Terrain. The Litter Spreader, Shavings Spreader and Compost Spreaders is an Endurance Spreader that is Option Rich and can be customized for your specific application.



### **Endurance Truck Mount Hydraulic Spreader**

The Endurance Truck Mount Hydraulic Spreader is perfect for Litter, Lime, Shavings, Compost, Manure and Organics Applications. This spreader is a Spinner Spreader so it will work great if you are looking for a Litter Spreader, Lime Spreader, Shavings Spreader, Compost Spreader, Manure Spreader or Organic Spreader. The BBI Binary manifold is STANDARD on all BBI Hydraulic

Power Spreaders so making use of Precision Agriculture electronics EASY!





### **Fertilizer and Lime Spreaders**

### **Orchard & Vineyard**



# Ag, Golf and Turf Spreaders CRICKET





# W Chranasa Indono polocer

The original single-axle, medium-capacity mechanical spreader with high clearance for mid-season top dress applications.





The ultimate mechanical, ground-wheel-drive spreader for a variety of medium-capacity nutrient applications.



### The Total III

Top dress for success with an all-new spinner system that boasts a 120 ft swath and flat spread pattern for a true 120 ft driving interval.



# **MagnaSpread**

The industry-leading hydraulic platform for application of fertilizer and lime, optimized for precision agriculture.

To Order Call Toll Free: Caldwell, ID 800-443-0809 • Pasco, WA 800-788-4453



### Chandler Compost / Litter Spreaders Lengths from 12' - 26'



PTO Mechanical Drive or Hydraulic Drive

Single Axle or Tandem Axle



### **Standard Features**

- Hopper Construction: Rails & Floor-3/16" Plate Sides & Ends-10 Ga. Mild Steel
  - Power Source: 540 PTO with 50:1 worm gear drive with 2" cross shaft
  - Conveyor: 34" wide bar type pintle chain with 3/8" thick bars on 11" centers
    - Spinners: Twin 24" disc, 1/4" thick plate with four 9" blades on each
      - Tandem axle suspension (Torsion Axles)
        - Lengths from: 10' to 26' available
- 10' 16' Units Standard Axles & Tires 12.5L x 15 Tires 6500 # rating each
- 18' 26' Units Standard Axles and Tires 16.5L x 16.1 10,000 # rating each
- Adjustable Flow Divider (for even spread patterns)
- ② Optional: 30" Spinners with 4 – blades each accurate Spread Patterns out to 50'
- ② Lengths from 12' 26'
- ② Optional: 700/40 –22.5 Flotation Tires with

16,000 # Torsion Axles

Optional: Dual Tandem

**Motor Gear Case** 





The Chandler Fertilizer and Lime Spreader is a durable, heavy duty and well designed unit to give long lasting, trouble-free service. The design and construction goes far beyond present standards and is striving for a lime or fertilizer spreader to meet the quality our customers demand. The superior design and construction, its low initial cost, its efficiency and ease of operation and economical maintenance make it the preferred spreader throughout the agri-business industry.

### **CHANDLER**

PULL TYPE FERTILIZER /L IME SPREADER



### FERTILIZER TENDERS



### CHANDLER "NURSE RITE" AUGER TENDERS



5 TON or 8 TON MODELS
SKID MONTED or
TRAILER MOUNTED
REAR DISCHARGER or
SIDE DISCHARGE AUGER



### 24-Ton Multi-hopper

Fertilizer Auger
Tender Hydraulically
Operated



To Order Call Toll Free: Caldwell, ID 800-443-0809 • Pasco, WA 800-788-4453

### **VALMAR**

### VALMAR AirFlo 8600 Pull-Type Fertilizer Spreader



Cover More Acres in Less Time
Accurate Metering System
Spread More Product between Fills
Ideal for Row Crop Farming
High Capacity PTO or Hydraulic Driven Fan
Choice of Boom Width 66' - 60' - 57' - 54'
Easy to Operate
Cover Crops

### **VALMAR AIRFLO 5500**



Stainless Steel Booms
1000 RPM PTO Fan Drive
Ground Driven Metering System
OR
Hydraulic Drive Metering
Apply Herbicides or Small Seeds
Ideal for Row Crop Application

**Unit Mount Seed & Fertilizer Applicators** 

### VALMAR 245 & 246 Granular Applicator



Rugged construction: Sturdy enough to withstand the rigors of commercial use

### **VALMAR 1255 BANDING OR BROADCAST APPLICATOR**





Broadcast or inter row banding boom with adjustable angle and height to provide different band application widths.

# **VALMAR** ST-6 & ST-8 STRIP TILL GRANULAR FERTILIZER APPLICATOR





Ideal for producers wanting to capitalize on the lower cost of granular fertilizer.

### **Unit Mount Seed & Herbicide Applicators**

# **VALMAR** 55 SERIES IMPLEMENT MOUNT GRANULAR APPLICATOR



3-Point hitch and tow behind mounting options for 55 series implements.

Designed to deliver unparalleled accuracy under a wide variety of ground conditions.



Cannon Sprayers

One of the most versatile sprayers providing excellent pest and disease protection for a wide variety of crops.

Cannon wide swath sprayers utilize a high-speed one direction air stream to deliver fine droplets to the crop target area. This high speed air is ideal for movement of the crop canopy, allowing the fine droplets to penetrate in areas not accessible when using a conventional boom sprayer or hand spraying technique and in many cases allowing you to reduce the total amount of gallons per acre applied. Spray swaths from as small as 15 feet up to 100 feet can be achieved depending on crop and wind conditions.

Jacto cannon sprayers can reduce your spray times by up to 75% and chemical usage by up to 50% versus hand spraying operations.

A very durable Jacto centrifugal pump delivers the spray solution from the tank to the outlet duct assembly that has both horizontal as well as vertical height adjustment.

Jacto cannon sprayers have proven very effective at fly control in dairy and feedlot operations.



Unsurpassed for coverage, durability and easy maintenance and are used for crop protection in a wide variety of crops such as orchards, vineyards, berries, hops, nurseries.

We utilize the world's finest Jacto ceramic cylinder high-pressure piston pumps, combined with our own control valves for the most efficient operation. All models except the Arbus 400-850 are equipped with double flip-over nozzles for quick changes of application rates.

Jacto axial fans are engineered and individually tailored to the specific model needs. They are equipped with adjustable pitch, fiberglass-reinforced nylon blades, air deflector vanes for even air distribution and a lockout mechanism so the fan can be turned off during filling, mixing, and hand-spraying.

Independent tests have shown Jacto Airblast Sprayers are unequalled when it comes to efficient and effective chemical delivery, canopy penetration and crop protection.



Arbus 1000 Arbus 1500 Arbus 2000 Arbus 270 Arbus 400 Arbus 500 Arbus 200













### **COMPACT EQUIPMENT**

### ARTICULATED WHEEL LOADERS

### Wheel Loader competence to the last detail.

### WL 34 Articulated Wheel Loader - Optimum power / fuel economy



The WL 34- equipped with a powerful 48HP Perkins T4F diesel engine

Operating weight 7,209lb Lifting force maximum 8,331 lb

Maneuverable to the tightest corner The articulated pendulum joint makes the machine uniquely maneuverable. Provides constant traction on uneven

around.





Operating weight 7,496 lbs. Lifting force max. 4,291 lbs. The WL 32 is equipped with a powerful Perkins 4-cylinder, Tier IV Final high performance diesel engine Available with either a 48-hp or 60-hp designed for maximum efficiency.

### **Articulated Wheel Loader offers Power and Performance:**



The extremely compact yet powerful WL 38 wheel loader is an excellent choice for any jobsite. Equipped with a 74-hp turbo charged Deutz Tier 4 Final diesel engine allowing the machine to achieve top speeds of 19 mph

Operating weight 9,260 lb Lifting force max. 4,850 lb

### WL 60



The WL 60, with its 101HP Perkins T4i engine, offers the speed and payload to handle nearly any jobsite it faces.

•Class leading 12 ft. pin height for easily managing high-side dump trucks.

### WL 52 Versatility, power and performance:



Lifting force maximum 6,755.5 lb

# WL 60 T TELOSCOPIC WHEEL LOADER

15' 10" PIN HEIGHT 9760 lbs. LIFT

Contact your G & R Sales Representative Today For Current Pricing and Options



# AL

5055 All Wheel Steer Loader

The 5055 all wheel steer wheel loader offers excellent maneuverability around the job site. This unit features a long wheelbase for smooth driving and easy handling even across the roughest terrain.

Counterweights are located far behind the rear axle for higher payloads and more stability.

Four-wheel drive steering offers excellent maneuverability, overall machine stability and increased payloads.

### ALL-WHEEL STEER WHEEL LOADERS

•Three steering modes: (All-wheel, 2-wheel & Crab) provide excellent maneuverability in any operating condition



The 8085 delivers exceptional weight to power ratio



8085T maximizes reach with telescopic boom •Telescopic boom offers extended reach of 15' 4" to the hinge pin

### **Telehandlers**

The TH522 groundengaging telehandler is designed to meet the digging demands of a wheel loader, the versatility of a skid steer and the lifting performance of a telehandler. With the hydraulically operated universal attachment plate, operating a wide variety of skid steer attachments is easy. Multiple load settings increase efficiency on the job site while the spacious operator station.



The TH627 ground-engaging telehandler offers a three-in-one machine concept that provides maximum versatility. Designed with a hydraulic skid steer plate, it delivers the digging capabilities of a wheel loader, the attachment versatility of a skid steer and the performance of a leading telehandler with a lift height of 18 ft. 5 in. and 5,500 lbs. of lifting capacity. The load management system maximizes performance by automatically adjusting the position of the load to increase cycle times and minimize tipping situations.

•Three steering modes (four-wheel, two-wheel and crab steering) are electronically synchronized and provide maximum maneuverability in any operating environment.

CONTACT YOUR G & R SALES REPRESENTATIVE FOR PRICING OPTIONS AND ATTACHMENT OPTIONS



### Medium Frame Skid Steer/Compact Track Loader

### Skid Steer **Standard Features**

The newest expansion for Wacker Neuson **Skid Steers and Compact Track Loaders** are our new Medium Frame Loaders. The new line consists of 4 skid steer loaders with Rated Operating Capacities (ROC) ranging from 1,600 lbs.- 2,100 lbs. and 2 compact track loaders with ROC's @ 50% of 2,800 lbs. and 3,100 lbs.

- Tier IV Final Diesel engine with maintenance-free after-treatment (DOC)
- Open ROPS Canopy
- Mechanical Hand-Foot Controls
- Mechanical Coupler
- 750cca Battery
- Single Speed Cooling Fan
- **Basic Interior**
- Standard Flow Hydraulics
- 2" Seatbelt
- Static Seat (Sliding Only, No Suspension)
- Single Speed Drive
- 3" Single Color Display
- Standard Work Lights
- 10 x 16.5 Standard Duty Tires



Kohler 1903 TDI 55HP, 3 Cylinders

**SW16** 

**SW20** 

RADIAL

VERTICAL



Kohler 2504 TDI 74HP, 4 Cylinders



**SW21** 



Kohler 2504 TDI 74HP, 4 Cylinders





Radial lift provides more horizontal reach, ideal for loading and unloading flat bed trucks. Because of the radial path, the arm's midway point extends further away from the machine that the vertical lift configuration.

The Radial Lift Arms on the SW16, SW17 provide a Hinge Pin Height of 118.1", and ST28 provide a Hinge Pin Height of 119.6". Vertical lift provides more reach at full height, ideal for dumping and loading trucks with high sides. Because of the vertical path of the arm, loading in tight quarters and using pallet forks also just became much easier.

The Vertical Lift Arms on the SW20 and SW21 provide a Class Leading Hinge Pin Height of 124". and ST31 provide a Class Leading Hinge Pin Height of 125.5".



### **Skid Steer Loaders**



SW24 Radial Lift Skid Steer Loader

The SW24 brings power and efficiency to any job site. This unit delivers 2,350 pounds of rated operating capacity at 50% and a lift height up to 125 inches. The machine is equipped with a 74.3 hp turbo-charged Perkins Tier IV Final engine. Available in both H-pattern and ISO joystick pilot controls, the machine can fit the preferences of any user.



SW 28 Vertical Lift Skid Steer

The SW 28 brings maximum reach making it ideal for loading and unloading. The SW 28 delivers 2,800 pounds of rated operating capacity at 50% and a lift height up to 134 inches. The machine is equipped with a 74.3 hp turbocharged Perkins Tier IV Final engine. Available in both H-pattern and ISO joystick control



ST 35 Radial Lift Track

The ST 35 radial lift track loader delivers power and maneuverability. This machine delivers 3,500 pounds of rated operating capacity at 50% and a lift height up to 125 inches. The ST 35 is powered by a 74.3 hp turbo-charged Perkins Tier IV Final engine. Available in both H-Patter and ISO joystick pilot controls.

### **Skid Steer Loaders**



ST45 Vertical Lift Compact Track Loader

The ST45 vertical lift compact track loader delives high operating capacity and extended lift height, making it ideal for digging and loading. The ST45 delivers 4,500 pounds of operating capacity at 5% and a lift height up to 134 inches. The machine is powered by a 74.3 hp turbo-charged Perkins Tier IV Final engine. The ST45 is available in both H- Pattern and ISO joystick pilot controls.

### **Wheel Dumpers**

The DW60 combines the power of a hydrostatic transmission Tier 4 Final Perkins engine with an industry leading, heavy duty design. With massive, impact-resistant box sections, this power swivel dumper offers high performance and a bucket engineered for durability. The DW60 is well balanced and easily moves its rated payload across the varying terrains of a job site. Full-time four-wheel drive ensures optimum maneuverability in difficult conditions.





This mid size dumper features a 6,600 lb payload capacity, power swivel material handling and hydrostatic permanent four wheel drive as standard. The hydrostatic drive system offers userfriendly controls, eliminating the need to change gears. The 3001 offers superior performance, the drive system automatically provides torque when and where it is needed. With no clutch to wear or gears to grind, hydrostatic drive eliminates the high parts and labor costs associated with replacing these components

To Order Call Toll Free: Caldwell, ID 800-443-0809 • Pasco, WA 800-788-4453



### **Tracked Conventional Tail Excavators**



Compact excavator 803 Dual power option integrated in the compact excavator Electro-hydraulic unit HPU8 In addition to the existing diesel engine, the compact excavator can be

operated emission-free via an electro-hydraulic unit



**ET 90** 

The minimum swing radius ET90 track excavator offers one of the smoothest and most powerful hydraulic systems available in its class. The 9-ton excavator comes with an air conditioned cab and a choice of short or long dipperstick and is powered by an economical 74.2-hp Deutz Tier 4 Final engine.

The ET145 is a compact excavator designed for power and productivity. This 14-ton excavator combines the productivity of a larger crawler excavator with the versatility and accessibility of a compact excavator. The 75-hp, Tier 4 Final turbo charged engine along with an optimized power train utilizes a constant power concept to deliver maximum horsepower and torque, regardless of the load on the engine.



ET 145



ET20

The ET20 is a productive and versatile digging machine with a maximum digging depth of 8' 10" and a strong breakout force of 4226 lbs. The Tier 4 Final engine delivers 17.2 net hp at 2,200 RPM for powerful digging, fast cycle times and quiet operation.

The minimum swing radius ET65 track excavator is powered by an economical 48.5-hp Perkins Tier 4 Final engine. It is one of the strongest machines in its weight class and performs more like a machine in the next size weight class. This 6.5-ton excavator offers one of the smoothest and most powerful hydraulic systems on the market.



### **Tracked Zero Tail Excavators**

The EZ17 compact excavator is the best performing zero tail model in its class.

Powered by a Tier 4 Final engine that offers excellent power, fuel economy and quiet operation.



•A telescopic undercarriage can be extended from 39" to 51" for greater lifting power and stability.

The EZ28 compact
excavator combines the
performance of a
conventional track
excavator with the
excellent maneuverability
of a zero tail swing machine.
When the housing is revolved,
the tail does not project over
the width of the tracks



Contact your G & R Sales Representative Today for Pricing and Options



### **INDUSTRY EXCLUSIVE**

 Optional Vertical Digging System (VDS).
 VDS enables progressive tilting of the superstructure by up to 15° to compensate for slopes, saving up to 25% material and time costs.

### **VDS - Vertical Digging System**



VDS enables progressive tilting of the superstructure by up to 15° with the push of a button, allowing the operator to compensate for slopes up to 27%. This makes precise vertical digging possible even on the most uneven of terrain. Cost-effectiveness and user comfort thus get a considerable boost.



### **Wheeled Excavators**

### EW65

The EW65 offers impressive power and speed with simple operation. Tier 4 Final Perkins engine offers excellent power and low fuel consumption.



The unit's compact size, speed up to 18.6 mph and mobility make it the ideal machine for a variety of applications that require the excavator to move around the job site or to and from the job site. This excavator saves time and money because it does not need to be transported on a truck.

### Tracked Zero Tail Excavators

The EZ28 compact excavator combines the performance of a conventional track excavator with the excellent maneuverability of a zero tail swing machine. When the housing is revolved, the tail does not project over the width of the tracks



EZ 28



This compact excavator combines the performance of a conventional track excavator with the excellent maneuverability of a zero tail swing machine. When revolved, the tail does not project over the width of the tracks.

Powered by an economical Tier 4 Final Perkins engine, this unit offers rubber tracks, dozer blade, boom mounted working light and control pattern change system.



CONTACT YOUR G & R SALES REPRESENTATIVE FOR PRICING OPTIONS AND ATTACHMENT OPTIONS



•Powerful Perkins 854 Tier 4 interim Turbo engine delivers 117-hp, which is 15% more power and 17% lower fuel consumption compared to its predecessor.

The 4-cylinder, 3.4 liter engine incorporates cutting edge technology including a common rail fuel injection system, charge-air cooler and diesel particulate filter





### Compaction

### 2 Stroke Rammer

Two-cycle rammers: Only from Wacker Neuson

Wacker Neuson rammers have long been accepted as the standard setters in the construction industry. They have been developed for maximum productivity, performance and durability.



### 4 Stroke Rammer Four-cycle rammers deliver outstanding performance

The outstanding features of Wacker Neuson's four-cycle rammers are the compact design and high performance. The long shoe stroke, high percussion rate and high stroke energy combined with fast advance travel achieve excellent results.

### **Diesel Rammer**

Diesel rammer built for extreme compaction jobs

Wacker Neuson's diesel rammer offers maximum production, performance and durability while providing you the convenience of standardizing your diesel fleet. The DS 70H is a well-balanced machine with low CO emissions and compact dimensions. It is ideally suited for the compaction of cohesive, mixed and granular soils.



### **Single direction Vibratory Plates**

VP- Value Plates - Soil and Asphalt

Vibratory plates offer functionality and performance at a value price. Available in asphalt and soil models.

WP-Premium Plates – Soil and Asphalt

Premium plates offer best-in-class components and features that set the industry standard for a variety of soil and asphalt applications.





### **Reversible Vibratory Plates**





### **INDUSTRY**

### **General Construction**

Utilities & Infrastructure

Landscaping

Government & Municipalities

Industrial / Oil & Gas

Concrete

Construction

**Agriculture** 

**Fertilizer** 

### **Concrete Technology**

»Internal Vibrators »External Vibrators »Frequency Converter »Trowels »Vibratory Screeds



### **WORKSITE TECHNOLOGY**

Pumps
»Self Priming Trash Pumps
»Diaphragm Pumps
»Submersible Pumps
»Dewatering Pumps





Heaters »Hydronic Surface Heaters

»Hydronic Air Heaters »Indirect Fired Air Heaters »Direct Fired Air Heaters »Flameless Air Heaters













### **TRAILERS**



# Tender Trailers

# Sprayer Traffers





# 1-ELLING TRAILERS





### **Sprayer Transport Trailers**





Contact your G & R Sales Representative Today for Pricing and Options



### SRT-2® Original Spool Roll Tarp Stainless Steel

- Most comprehensive stainless steel tarping system on the market
- Quick Release Tarp Stops Powder Coated with Stainless Steel Base
- 14" Deep, 7" Standard Rise Stainless Steel End Caps, 12" Rise-optional
- 18 oz. Tarp in Black, White, Gray, Ocean Blue, Red, Orange, Yellow, Green or Brown
- 3" Aluminum Roll Tube
- 1 Ridge Strap SST
- · Stainless Steel Bows included
- Electric Optional



### EZ-LOC® Roll Tarp Stainless Steel

- Quick Release Tarp Stops
- 14" Deep, 7" Standard Rise Stainless Steel End Caps, 12" Rise-optional
- 18 oz. Tarp in Black, White, Gray, Ocean Blue, Red, Orange, Yellow, Green or Brown
- 2" Aluminum Roll Tube
- 1 Ridge Strap SST
- SST Bows included on Farm Truck Boxes Only, Bows not included on Semi Trailers
- · Electric-Optional

### AUTOLOCK® Electric Tarp

- High output electric motor
- Quick Release Tarp Stops
- 14" Deep, 7" Rise Galv. End Caps (front and rear side mounted) Some trailers may require OEM specific radius caps.
- 18 oz. Tarp in Black, White, Gray, Ocean Blue, Red, Orange, Yellow, Green or Brown
- 3" Aluminum Roll Tube
- 2 Ridge Straps
- · Bows not included



### TARPING SYSTEMS

### CHOOSING YOUR ELECTRIC TARPING SYSTEM

|                                    | A.   | В.   | C.                               | D.  | E.                     | F.        |
|------------------------------------|--|--|----------------------------------|---|------------------------|-----------|
|                                    | Roltec <sup>TM</sup><br>Electric<br>Conversion<br>w/ Cable<br>Return | EZ-LOC** Electric Conversion with Cable Return | SRT-2°<br>Electric<br>Conversion | Roltec™<br>Single<br>Arm with<br>Rear Cable<br>Return | Roltec™<br>Dual<br>Arm | Autolock* |
| Farm Box                           | Good   | Better   | Best                             | -   | -                      | E         |
| Grain Trailer 25'-40'              | Good   | Good   | -                                | -   | Better                 | Best      |
| Grain Trailer 41'-53'              | -  | -  | -                                | -   | Better                 | Best      |
| Grain Trailer SST                  | (×   | Best   | -                                | -   | -                      | -         |
| Grain Trailer w/ Rear<br>Discharge | Ť.   |  | -                                | Best  | 7                      | Best      |
| Pup Trailer                        | Good   | Good   | Better                           | -   | Better                 | Best      |
| Grain Cart                         | ×  | -  | Best                             | -   | -                      | -         |
| Seed Tender Trailer                | Good   | Better   | Best                             | 2   | -                      | 2         |
| Fertilizer Tender Trailer<br>SST   |  | Better   | Best                             | -   | -                      |           |
| Fertilizer Spreader SST            | -  | Better   | Best                             | -   |                        | В.        |
| Belly Dump                         | -  |  | Best                             | - 4   | -                      | 18        |





### G&R Manufactured Three-Point Sprayers





### **Three-Point Sprayers**

- Heavy duty frame with category I or II hitch pins
- Many Sizes available
- Completely assembled
- Wide range of pumping options
- Chemical resistant polyethylene tank
- Powder coated paint
  - •Pump kits include:

Pressure regulator, Line strainer, 3-way shut-off valve, Drain plug, Pressure gauge, Booster bypass, and Agitation





### **G&R Manufactured Skid Sprayers**



### **Skid Sprayers**

Heavy duty C Channel frame
Chemical resistant polyethylene tank
Pump kits include polypropylene fittings
Easy access tank shut- off & strainer
Rubber mounts on engine models to eliminate vibration
Quick coupler on drain or fill
Powder coated paint







### **CUSTOM MADE**

TRUCK MOUNT DE-ICER



# TRUCK MOUNTED SKID SPRAYERS



### Side Mount Sprayers

### G&R Manufactured Side Mount Sprayers





### **Side Mount Sprayers**

•All pump kits include:
-Poly Quick couplers for easy removal

-Pressure Gauge
-Tank shut off valves
-Stainless steel manifolds
•Chemical resistant polyethylene tank
•Frame mounted control stand
•Heavy Duty Powder coated frame

### **G&R Manufactured Front Mount Sprayers**

### **CUSTOM FRONT TRACTOR MOUNT**

- Designed for Case-IH, John Deere, Caterpillar and New Holland.
  360, 500 and 600 gallon capacities.
- •The teardrop design maximizes the operator's forward vision and access to the cab.
  - 10" fill opening, deep bottom sump for complete product withdrawal.
    Three year tank warranty.
  - •Complete kit includes two tanks, saddles, straps,sparge tubes and mounting brackets.
  - •Pump and plumbing kits sold separately.





# **Custom Sprayers**

# G & R Manufactured Custom Sprayers

### **UTV Sprayers**



**Truck Mount 4 Tank 4 Hose Reel** 



Contact G & R Today For Custom Sprayer Needs





### <u>V / UTV SPRAYERS</u>



ESTATE SPOT I 15 GALLON TANK-1.8 G.P.M. PUMP ESTATE SPOT III 25 GALLON TANK-1.8 G.P.M PUMP

15 GALLON TANK-1.8 G.P.M PUMP LIL SPOT I 15 GALLON TANK-1.8 G.P.M PUMPW/AGITATION LIL SPOT I-2 LIL SPOT 1-3 15 GALLON TANK-3.0 G.P.M PUMPW/ AGITATION LIL SPOT 1-4 15 GALLON TANK-4.0 G.P.M. PUMPW/ AGITATION LIL SPOT 1-5 15 GALLON TANK-5.0 G.P.M. PUMPW/ AGITATION

LIL SPOT III 25 GALLON TANK-1.8 G.P.M. PUMP LIL SPOT III-2 25 GALLON TANK-1.8 G.P.M. PUMPW/ AGITATION

LIL SPOT III-3 25 GALLON TANK-3.0 G.P.M. PUMPW/ AGITATION LIL SPOT III-4 25 GALLON TANK-4.0 G.P.M. PUMP W/ AGITATION LIL SPOT III-5 25 GALLON TANK-5.0 G.P.M. PUMPW/ AGITATION

LIL SPOT IV 40 GALLON TANK-1.8 G.P.M. PUMP LIL SPOT IV-2

40 GALLON TANK-1.8 G.P.M. PUMPW/ AGITATION LIL SPOT IV-3 40 GALLON TANK-3.0 G.P.M. PUMP W/ AGITATION 40 GALLON TANK-4.0 G.P.M. PUMPW/ AGITATION LIL SPOT IV-4 LIL SPOT IV-5 40 GALLON TANK-5.0 G.P.M. PUMPW/ AGITATION

LIL SPOT V 60 GALLON TANK-1.8 G.P.M. PUMP

60 GALLON TANK-1.8 G.P.M. PUMPW/ AGITATION LIL SPOT V-2 LIL SPOT V-3 60 GALLON TANK-3.0 G.P.M. PUMPW/ AGITATION LIL SPOT V-4 60 GALLON TANK-4.0 G.P.M. PUMPW/ AGITATION LIL SPOT V-5 60 GALLON TANK-5.0 G.P.M. PUMPW/ AGITATION

### The "EZ RIDER "Sprayer





"EZ RIDER" Booms

# Boomiess no



LILBN1200PS-2 LILBN1870PL LILBNXP10-2



24 ft. half spray plastic boomless nozzles 30 ft. full spray plastic boomless nozzles

10 ft. boomless nozzle kit w/ 1165 SS nozzles

LILBN1165-2 LILBN1160-2 32 ft. boomless nozzle kit w/ 1160 SS nozzles LILBN1250-2 32 ft. boomless nozzle kit w/ 1250 SS nozzles

Contact G & R Today For All Your Custom Sprayer Needs





We Can Manufacture To Meet Your Needs Call Us Today!

### 1000 Gallon and 1400 Gallon Tank / Trailer



Includes:
14,000# Tandem Axle
Light Kit
Heavy Duty Jack
Brakes on Both Axles

# Double Cone Bottom Tank / Trailer



Includes:
(2) - 3000 Gallon Snyder Tanks
2" X 6" Main Frame Tube
3500 lb. Spindle, 7000 lbs. GVWR
Hydraulic Jack, Safety Chains
Platform to mount Transfer Pump
Powder Coat Finish

# Triple Cone Bottom Tank / Trailer



Includes: (3)-3000 Gallon Snyder Tanks

**Custom Built Tank / Trailers** 









Snyder's vertical tanks are strong and versatile enough for your bulk storage needs. These tough, lightweight tanks come in a variety of styles and sizes from 65 gallons to 16,500 gallons. Snyder vertical tanks feature stable, flat bottoms, maximum drainage siphon assemblies and molded-in tie down lugs.

### **CONE BOTTOM TANKS**

Snyder's mix tanks are available in sizes from 17 gallons to 110 gallons, while our cone bottom storage tanks hold from 475 gallons to 11,850 gallons. The 15°, 30° and 45° cone options provide fast discharge and complete drainage, and both our mix tanks and storage tanks feature engineered, welded steel stands.





### HORIZONTAL TANKS

Snyder manufactures a wide line of applicator tanks in sizes from 8 gallons to more than 2,600 gallons and a variety of styles including lawn and garden, horizontal, elliptical, champion, sidemount and spherical. All tanks feature manways for easy filling, ultraviolet inhibitors to protect the tank and its contents



# Fittings, Steel & Accessories Snyder offers a variety of fittings. Types of materials available include polyethylene (standard), Poly Pro, PVC, and Stainless Steel.



### Leg & Elliptical Leg Tanks

Perfect for nurse applications, Snyder leg tanks eliminate the need for steel mounting saddles and cradles and come in a variety of sizes from 30 gallons to 3000 gallons. Snyder leg tanks feature screw-on and hinged leak-proof lids, recessed areas for tie downs, molded-in gallonage markers and sturdy self-supporting molded-in legs.

### Ace Roto Mold

### **Elliptical Tanks**

The tanks are manufactured from medium-density polyethylene with U.V. stabilizers and are designed for containment of liquids of up to 1.7 specific gravity.





Free Standing Horizontal Bulk Storage Tanks

Utility Tanks – Flat Bottom

Rectangle Tanks – Flat Bottom







Pick Up Tanks





Cut Away Tanks





Tear Drop Tanks





### IT'S SO MUCH MOWER

# True ZeroTurn<sup>™</sup> FrontMount<sup>™</sup> Mowers

# True ZeroTurn<sup>™</sup> MIDMOUNT<sup>™</sup> Mowers







600 Series **Air-Cooled Gas** Model 616T Model 623T 700 Series **Air-Cooled Gas** Model 725KT Model 727T EFI Model 729BT Model 735BT **Liquid-Cooled Gas** Model 729T **Liquid-Cooled Diesel** Model 721DT Model 725DT 900 Series **Liquid-Cooled Gas** 

Model 932







100V Series **Air-Cooled Gas** Model 124V Model 125V Model 126V 200V Series **Air-Cooled Gas** Model 225V Model 226V 200 Model 225 300 Series **Air-Cooled Gas** Model 327 EFI Model 329B Model 335 **Liquid-Cooled Gas** Model 329 **Liquid-Cooled Diesel** Model 321D Model 325D 400 Series **Liquid-Cooled Gas** 

Model 432

# **Credit Application**

### **CREDIT APPLICATION**

| CUSTOMER NAME:   |  |                        |                |       |  |  |
|--|--|------------------------|----------------|-------|--|--|
| MAILING ADDRESS:   |  |                        |                |       |  |  |
| SHIPPING ADDRESS:  |  |                        |                |       |  |  |
| SHIPPING ADDRESS:  PHONE NUMBER:  PERSON TO CONTACT:  TITLE: |  |                        |                |       |  |  |
| PERSON TO CONTACT: TITLE:                                    |  |                        |                |       |  |  |
| CC   | PARPORATIONPA  | ARTNERSHIP             | PROPRIETORSHIP |       |  |  |
| TYPE OF BUSINESS:  |  |                        |                |       |  |  |
| EMPLOYER ID # OR SS  | CYPE OF BUSINESS: YEARS IN BUSINESS: |                        |                |       |  |  |
| EMAIL ADDRESS: WEB SITE:                                     |  |                        |                |       |  |  |
|  | OWNE   | R'S - OFFICER          | <u>S</u>       |       |  |  |
| NAME:  |  | ADDRESS:               |                |       |  |  |
| TITLE:   | AME: ADDRESS:<br>TLE: CITY-ST-ZIP:   |                        |                |       |  |  |
| NAME: ADDRESS:   |  |                        |                |       |  |  |
| TITLE:   |  | CITY-ST-ZIP:           |                |       |  |  |
|  | TRAD   | E REFERENCE            | <u>S</u>       |       |  |  |
| NAME   | ADDRESS  |                        | PHONE          | FAX   |  |  |
|  |  |                        |                |       |  |  |
| NAME & CONTACT   |  | K REFERENCE<br>ADDRESS |                | PHONE |  |  |
| PURCHASE ORDERS R<br>PERSONS AUTHORIZE                       |  |                        |                |       |  |  |
| PURCHASES TAXABLE  |  | ESALE TAX # _          |                |       |  |  |

**SEE NEXT PAGE: Questions To Be Answered** 

To Order Call Toll Free: Caldwell, ID 800-443-0809 • Pasco, WA 800-788-4453 www.gandragproducts.com

### **Credit Application**

I hereby authorize G&R AG PRODUCTS, INC. to correspond with all references furnished for credit information. I agree to pay all finance charges assessed on my account. I further agree not to take payment discounts on invoices that are past the due date. No discounts will be allowed on current invoices if there are unpaid invoices, finance charges or disallowed discounts.

All accounts are due and payable per the terms listed on each invoice. All past due accounts are subject to a finance charge of 1.5% per month or 18% annual percentage rate. I agree to pay all collection expenses, including a reasonable attorneys fee if my account is submitted for collections.

All sales are conditioned and retained by G&R AG PRODUCTS, INC. until payment is made in full.

I here by agree to all above terms and agreements and certify that all above information is correct to the best of my knowledge.

| SIGNED: | TITLE: |  |
|---------|--------|--|
| DATE:   |        |  |

### ACCOUNTS 60 DAYS PAST DUE MAY AUTOMATICALLY BE PLACED ON C.O.D

**IDAHO** 

G & R AG PRODUCTS, INC. PO BOX 340 CALDWELL, ID 83606 (208) 454-2288 (208) 454-2255 FAX WASHINGTON

G & R AG PRODUCTS, INC. PO BOX 966 PASCO, WA 99301 (509) 545-5855 (509) 547-2163 FAX

To Order Call Toll Free: Caldwell, ID 800-443-0809 • Pasco, WA 800-788-4453

www.gandragproducts.com

### MANUFACTURES REPRESENTED BY G & R AG. PRODUCTS









PENTAIR

























IYPRO'











Behnke Enterprises, Inc.
































# "Headquarters For All Your Spraying Needs"



### Caldwell

906 SIMPLOT BLVD. P.O. BOX 340 CALDWELL, ID. 83607 Phone: (208) 454-2288 Toll Free: (800)443-0809 Fax: (208) 454-2255

### **Pasco**

721 N. OREGON AVE...
P.O. BOX 966
PASCO, WA. 99301
Phone: (509) 545-5855
Toll Free: (800) 788-4453
Fax: (509) 547-2163

To Order Call Toll Free: Caldwell, ID 800-443-0809 Pasco, WA 800-788-4453